



# KLINGER TOPLINE K49

Gore™ GFO® Packing



High performance multiservice compression packing for both valves & pumping applications. Klingerlock braided from Gore GFO® filament yarns.

Klinger TopLine packing range has been selected to provide users with gland sealing products that meet today's demanding services, offering effective and trouble-free sealing during application. To achieve this goal we have selected the best materials and the best production methods.

## GENERAL PROPERTIES

- » Virtually resistant to all media including strong acids and alkalis.
- » Klingerlock braided from Gore™ GFO®, PTFE filaments, which have been specially treated to incorporate a graphite based lubricant.
- » Due to its wide service capabilities K49 TopLine packing offers the user a packing material with excellent sealing life and the option of reducing the variety of packings that must be held as stock.


## TESTS AND CERTIFICATIONS

- » WRAS Approval for use with potable water

## AVAILABILITY

SIZE (MM)	LENGTH (M)	SIZE (MM)	LENGTH (M)
3.2 x 3.2	8	12.5 x 12.5	8
5.0 x 5.0	8	14.0 x 14.0	8
6.5 x 6.5	8	16.0 x 16.0	8
8.0 x 8.0	8	19.0 x 19.0	8
9.5 x 9.5	8	22.0 x 22.0	8
11.0 x 11.0	8	25.0 x 25.0	8

## APPLICATION GUIDELINES



- Caution: May be suitable but essential that you refer to Klinger for advice
- Usually Satisfactory, but suggest you refer to Klinger for advice
- Usually Satisfactory to Use Without Reference

NOTE: Chemical compatibility must be considered in all cases.

## TYPICAL SPECIFICATIONS

PROPERTIES	VALUES
Min. Temperature	-240°C
Max. Steam Temperature	280°C
Max. Temperature	280°C
Max. Static Pressure	250 Bar
Max. Dynamic Pressure	20 Bar
Max. Reciprocating pressure	200 Bar
Max. Speed	18 m/s
pH Range	0-14

This packing should not be subjected to maximums of temperature, pressure and speed simultaneously.