

Type: 541

Check valve in stainless steel 316


RG - female threaded, Spring loaded

Application: water, liquids and gases

» Universal mounting

General Data

Type:	541
Material:	AISI 316
Pressure class:	PN 16
Disc:	316
Sealing:	FKM(viton). Option EPDM, PTFE or NBR
Spring:	AISI316
Connection:	Female threaded acc. to ISO 7/1
Temperature:	NBR -25°C to 90°C EPDM -20°C to 110°C FKM -20°C to 150°C PTFE -20°C to 200°C



541

Item No.	DIMENSIONS (mm)		WEIGHT
	DN	L / H	
60601008	1/4"	32/54	0,125
60601010	3/8"	32/54	0,115
60601015	1/2"	32/54	0,095
60601020	3/4"	44/70	0,129
60601025	1 "	53/84	0,191
60601032	1.1/4"	62/99	0,281
60601040	1.1/2"	78/119	0,390
60601050	2 "	89/123	0,704
60601065	2.1/2"	113/147	1,4
60608061	3 "	132/166	2,1
-	4 "	167/193	3,4

KLINGER Portugal, Ltd.
Via José Régio, 36
Centro Empresarial Vilar do Pinheiro
4485-860 Vila do Conde
T: +351 229 470 910
E-mail: geral@klinger.pt