

SA 07.2 – SA 16.2

AUMA NORM

Technical data Multi-turn actuators for open-close duty with 3-phase AC motor

General information

AUMA NORM multi-turn actuators require electric controls. For sizes SA 07.2 – SA 16.2, AUMA offers AM or AC actuator controls. These can also easily be mounted to the actuator at a later date.

Type	Output speed rpm		Torque range ¹⁾			Number of starts	Valve attachment ²⁾			Handwheel		Weight ³⁾
	50 Hz	60 Hz	Min. [Nm]	S2 - 15 min Max. [Nm]	S2 - 30 min Max. [Nm]		Starts Max. [1/h]	Standard EN ISO 5210	Option DIN 3210	Max. Ø rising stem [mm]	Ø [mm]	
SA 07.2	4	4.8	10	30	20	60	F07 F10	– G0	26 34 ⁴⁾	160	11 : 1	19
	5.6	6.7									8 : 1	
	8	9.6									11 : 1	
	11	13									8 : 1	
	16	19									11 : 1	
	22	26									8 : 1	
	32	38									11 : 1	
	45	54									8 : 1	
	63	75									11 : 1	
	90	108									8 : 1	
	125	150		5.5 : 1								
180	216	25	4 : 1	20								
4	4.8	20	60		40	60	F07 F10	– G0	26 34 ⁴⁾	160	11 : 1	
5.6	6.7										8 : 1	
8	9.6										11 : 1	
11	13										8 : 1	
16	19										11 : 1	
22	26										8 : 1	
32	38										11 : 1	
45	54										8 : 1	
63	75										11 : 1	
90	108										8 : 1	
125	150		5.5 : 1	21								
180	216	50	30		4 : 1							
4	4.8	40	120		90	60	F10	G0	40	200	11 : 1	
5.6	6.7										8 : 1	
8	9.6										11 : 1	
11	13										8 : 1	
16	19										11 : 1	
22	26										8 : 1	
32	38										11 : 1	
45	54										8 : 1	
63	75										11 : 1	
90	108			8 : 1								
125	150		5.5 : 1	22								
180	216	100	70		4 : 1							
4	4.8	100	250		180	60	F14	G1/2	58	315	11 : 1	
5.6	6.7										8 : 1	
8	9.6										11 : 1	
11	13										8 : 1	
16	19										11 : 1	
22	26										8 : 1	
32	38										11 : 1	
45	54										8 : 1	
63	75										11 : 1	
90	108			8 : 1								
125	150		5.5 : 1	44								
180	216	200	140		4 : 1							
4	4.8	100	250		180	60	F14	G1/2	58	315	11 : 1	
5.6	6.7										8 : 1	
8	9.6										11 : 1	
11	13										8 : 1	
16	19										11 : 1	
22	26										8 : 1	
32	38										11 : 1	
45	54										8 : 1	
63	75										11 : 1	
90	108			8 : 1								
125	150		5.5 : 1	48								
180	216	200	140		4 : 1							

SA 07.2 – SA 16.2 AUMA NORM

Technical data Multi-turn actuators for open-close duty with 3-phase AC motor

Type	Output speed rpm		Torque range ¹⁾			Number of starts	Valve attachment ²⁾			Handwheel		Weight ³⁾
	50 Hz	60 Hz	Min. [Nm]	S2 - 15 min Max. [Nm]	S2 - 30 min Max. [Nm]		Starts Max. [1/h]	Standard EN ISO 5210	Option DIN 3210	Max. Ø rising stem [mm]	Ø [mm]	
SA 14.6	4	4.8	200	500	360	60	F14	G1/2	58	400	11 : 1	46
	5.6	6.7									8 : 1	
	8	9.6									11 : 1	
	11	13									8 : 1	
	16	19									11 : 1	
	22	26									8 : 1	
	32	38									11 : 1	
	45	54									8 : 1	
	63	75									11 : 1	
	90	108									8 : 1	
	125	150									5.5 : 1	
SA 16.2	4	4.8	400	1,000	710	60	F16	G3	77	500	11 : 1	67
	5.6	6.7									8 : 1	
	8	9.6									11 : 1	
	11	13									8 : 1	
	16	19									11 : 1	
	22	26									8 : 1	
	32	38									11 : 1	
	45	54									8 : 1	
	63	75									11 : 1	
	90	108									8 : 1	
	125	150									5.5 : 1	
SA 16.2	180	216	400	800	570	60	F16	G3	77	500	4 : 1	83
	180	216		800	570						4 : 1	

- 1) The tripping torque is adjustable for directions OPEN and CLOSE within the indicated torque range.
- 2) Indicated flange sizes apply for output drive types A and B1. Refer to separate dimension sheets for further output drive types.
- 3) Indicated weight includes AUMA NORM multi-turn actuator with 3-phase AC motor, electrical connection in standard version, output drive type B1 and handwheel.
- 4) Stem diameter for rising stem in combination with AUMA stem protection tube made of PMMA max. 30 mm.

Features and functions																																																																			
Type of duty	Standard: Short-time duty S2- 15 min, classes A and B according to EN ISO 22153 Option: Short-time duty S2- 30 min, classes A and B according to EN ISO 22153 For nominal voltage and +40 °C ambient temperature and at load with 35 % of the max. torque.																																																																		
Motors	3-phase AC asynchronous squirrel-cage motor, type IM B9 according to IEC 60034-7, IC410 cooling procedure according to IEC 60034-6																																																																		
Mains voltage, mains frequency	Standard voltages: <table border="1"> <thead> <tr> <th colspan="12">3-phase AC Voltages/frequencies</th> </tr> <tr> <th>Volt</th> <th>220</th> <th>230</th> <th>380</th> <th>380</th> <th>400</th> <th>400</th> <th>415</th> <th>440</th> <th>460</th> <th>480</th> <th>500</th> </tr> </thead> <tbody> <tr> <td>Hz</td> <td>60</td> <td>50</td> <td>50</td> <td>60</td> <td>50</td> <td>60</td> <td>50</td> <td>60</td> <td>60</td> <td>60</td> <td>50</td> </tr> </tbody> </table> Special voltages: <table border="1"> <thead> <tr> <th colspan="10">3-phase AC Voltages/frequencies</th> </tr> <tr> <th>Volt</th> <th>220</th> <th>440</th> <th>525</th> <th>575</th> <th>575</th> <th>600</th> <th>660</th> <th>690</th> <th></th> </tr> </thead> <tbody> <tr> <td>Hz</td> <td>50</td> <td>50</td> <td>50</td> <td>50</td> <td>60</td> <td>60</td> <td>50</td> <td>50</td> <td></td> </tr> </tbody> </table> Further voltages on request Permissible variation of mains voltage: ±10 % Permissible variation of mains frequency: ±5 %	3-phase AC Voltages/frequencies												Volt	220	230	380	380	400	400	415	440	460	480	500	Hz	60	50	50	60	50	60	50	60	60	60	50	3-phase AC Voltages/frequencies										Volt	220	440	525	575	575	600	660	690		Hz	50	50	50	50	60	60	50	50	
3-phase AC Voltages/frequencies																																																																			
Volt	220	230	380	380	400	400	415	440	460	480	500																																																								
Hz	60	50	50	60	50	60	50	60	60	60	50																																																								
3-phase AC Voltages/frequencies																																																																			
Volt	220	440	525	575	575	600	660	690																																																											
Hz	50	50	50	50	60	60	50	50																																																											
Overvoltage category	Category III according to IEC 60364-4-443																																																																		
Insulation class	Standard: F, tropicalized Option: H, tropicalized																																																																		

SA 07.2 – SA 16.2

AUMA NORM

Technical data Multi-turn actuators for open-close duty with 3-phase AC motor

Features and functions	
Motor protection	Standard: Thermoswitches (NC)
	Option: PTC thermistors (according to DIN 44082) PTC thermistors additionally require a suitable tripping device in the actuator controls.
Self-locking	Self-locking: Output speeds up to 90 rpm (50 Hz), 108 rpm (60 Hz) NOT self-locking: Output speeds from 125 rpm (50 Hz), 150 rpm (60 Hz) Multi-turn actuators are self-locking, if the valve position cannot be changed from standstill while torque acts upon the output drive.
Motor heater (option)	Voltages: 110 – 120 V AC, 220 – 240 V AC or 380 – 480 V AC
	Power depending on the size 12.5 – 25 W
Manual operation	Manual drive for setting and emergency operation, handwheel does not rotate during electrical operation.
	Option: Handwheel lockable Handwheel stem extension Power tool for emergency operation with square 30 mm or 50 mm
	Indication whether manual operation is active/not active via single switch (1 change-over contact)
Electrical connection	Standard: AUMA plug/socket connector with screw-type connection
	Option: Terminals or crimp connection Gold-plated control plug (sockets and pins)
Threads for cable entries	Standard: Metric threads
	Option: Pg-threads, NPT-threads, G-threads
Terminal plan	TPA00R1AA-101-000 (basic version)
Valve attachment	Standard: B1 according to EN ISO 5210
	Option: A, B2, B3, B4, C, D according to EN ISO 5210 A, B, D, E according to DIN 3210 C according to DIN 3338
	Special valve attachments: AF, AK, AG, B3D, ED, DD, IB1, IB3 A prepared for permanent lubrication of stem

Electromechanical control unit

Limit switching	Counter gear mechanism for end positions OPEN and CLOSED Turns per stroke: 1 to 500 (standard) or 1 to 5,000 (option)
	Standard: Single switch (1 NC and 1 NO) for each end position, not galvanically isolated
	Options: Tandem switch (2 NC and 2 NO) for each end position, switches galvanically isolated Triple switch (3 NC and 3 NO) for each end position, switches galvanically isolated Intermediate position switches (DUO limit switching), adjustable for each direction of operation
Torque switching	Torque switching adjustable for directions OPEN and CLOSE
	Standard: Single switch (1 NC and 1 NO) for each direction, not galvanically isolated
	Option: Tandem switch (2 NC and 2 NO) for each direction, switches galvanically isolated
Switch contact materials	Standard: Silver (Ag)
	Option: Gold (Au), recommended for low voltage actuator controls
Position feedback signal, analogue (options)	Potentiometer or 0/4 – 20 mA (electronic position transmitter)
Mechanical position indicator (option)	Continuous indication, adjustable indicator disc with symbols OPEN and CLOSED
Running indication	Blinker transmitter
Heater in switch compartment	Standard: Self-regulating PTC heater, 5 – 20 W, 110 – 250 V AC/DC
	Options: 24 – 48 V AC/DC or 380 – 400 V AC
	A resistance type heater of 5 W, 24 V AC is installed in the actuator in combination with AM or AC actuator controls.

SA 07.2 – SA 16.2 AUMA NORM

Technical data Multi-turn actuators for open-close duty with 3-phase AC motor

Electronic control unit (option, only in combination with AC actuator controls)	
Non-Intrusive setting	Magnetic limit and torque transmitter (MWG) Turns per stroke: 1 to 500 (standard) or 10 to 5,000 (option)
Position feedback signal	Via actuator controls
Torque feedback signal	Via actuator controls
Mechanical position indicator (option)	Continuous self-adjusting indication with symbols OPEN and CLOSED
Running indication	Blinking signal via actuator controls
Heater in switch compartment	Resistance type heater with 5 W, 24 V AC
Service conditions	
Use	Indoor and outdoor use permissible
Mounting position	Any position
Installation altitude	≤ 2 000 m above sea level > 2,000 m above sea level, on request
Ambient temperature	Standard: -30 °C to +70 °C Options: -40 °C to +80 °C -60 °C to +60 °C 0 °C to +120 °C
Humidity	Up to 100 % relative humidity across the entire permissible temperature range
Enclosure protection in accordance with IEC 60529	Standard: IP68 with AUMA 3-phase AC motor For special motors, differing enclosure protection is possible Option: Terminal compartment additionally sealed against interior of actuator (double sealed) According to AUMA definition, enclosure protection IP68 meets the following requirements: <ul style="list-style-type: none"> • Depth of water: Maximum 8 m head of water • Continuous immersion in water: maximal 96 hours • Up to 10 operations during immersion
Pollution degree according to IEC 60664-1	Pollution degree 4 (when closed), pollution degree 2 (internal)
Vibration resistance according to IEC 60068-2-6	2 g, 10 to 200 Hz (AUMA NORM), 1 g, 10 to 200 Hz (for actuator with mounted AM or AC AUMA actuator controls) Resistant to vibration during start-up or for failures of the plant. However, a fatigue strength may not be derived from this. Indications apply to actuator with AUMA 3-phase AC motor and AUMA plug/socket connector. They are not valid in combination with gearboxes.
Corrosion protection	Standard: KS: Suitable for use in areas with high salinity, almost permanent condensation, and high pollution. Options: KX: Suitable for use in areas with extremely high salinity, permanent condensation, and high pollution. KX-G : same as KX, however aluminium-free version (outer parts)
Coating	Two-layer powder coating Two-component iron-mica combination
Colour	Standard: AUMA silver-grey (similar to RAL 7037) Option: Available colours on request
Lifetime	AUMA multi-turn actuators meet or exceed the lifetime requirements of EN ISO 22153. Detailed information can be provided on request.
Noise level	< 72 dB (A)
Further information	
EU Directives	Machinery Directive 2006/42/EC Low Voltage Directive 2014/35/EU EMC Directive 2014/30/EU RoHS Directive 2011/65/EU
Reference documents	Dimensions SA 07.2 – SA 16.2/SAR 07.2 – SAR 16.2 Electrical data SA 07.2 – SA 16.2